

Connector PowerTOP® Xtra with ErgoCONTACT

Part no. 14516




- screw terminals [ErgoCONTACT](#)
- [X-CONTACT](#)
- ergonomic enclosure design with nubbed grip areas
- rubberised cable gland with sealing
- strain relief and protection against kinking
- thread lock and safety slid
- area for self-adhesive labels

Technical specifications

| | |
|---------------------------|-------------------------------|
| Ampere | 32 A |
| Poles | 4 p |
| Voltage | 400 V |
| Clock position | 6 h |
| Hertz | 50-60 Hz |
| Connection technology | Screw terminals, ErgoCONTACT® |
| Contact | X-CONTACT® |
| Protection type | IP 54 |
| Declaration of Conformity | EAC |

Drawing



| Drawing 3 MB 79 | Amp. Poles | 16 | | 32 |
|--------------------------------------|---------------|------|------|-----|
| | | 3 | 5 | 5 |
| Dim. in mm | a | 165 | 174 | 209 |
| | b | 55 | 69 | 80 |
| | h | 72 | 98 | 108 |
| | y | 14.5 | 16 | 22 |
| Terminal for cond. cross | | 1 | 1 | 2.5 |
| section (mm ²) min.-max. | | -2.5 | -2.5 | -6 |