

AMAXX® combination unit

Part no. 920700




- pre-wired for installation
- enclosure and insert made of AMAPLAST
- fusing behind a transparent cover
- enclosure front cover electric grey RAL 7035
- hinged to the side (except enclosure size 130 x 225 mm and 650 x 112.5 mm)
- fusing behind a transparent cover

Technical specifications

CEE 16 A, 3 p, 110 V	2	
Fusing		• 1 RCD 25 A, 2 p, 0.03 A
Pre-fuse max.	16 A	
InA	25 A	
RDF	1	
Connection / feeder cable		• for 1 cable up to 3 x 10 mm ²
Protection type	IP 67	
Shutter	false	
Enclosure material	Plastic	
Weight	2490 g	

Drawing



Drawing 1 MB 521

Depth dimensions at various fittings.

Receptacles	Degrees	Depth
SCHUKO® 16A, 230 V	IP 44	175 mm
	IP 67	194 mm
CEE 16A, 3p, 230V	IP 44	204 mm
	IP 67	205 mm
CEE 16A, 5p, 400V	IP 44	209 mm
	IP 67	213 mm
CEE 32A, 5p, 400V	IP 44	221 mm
	IP 67	227 mm
CEE 63A, 5p, 400V	IP 44	248 mm
	IP 67	248 mm

Cable entries: closed for cut out. 2 x M 32 each on top and bottom, 2 x M 20 each on top and bottom for cut out.