

- Fully load rated AC22A 415V.
- BSEN60947-3 Conformity.
- Door interlocked padlockable handles on hinged units.
- Alternative pole configurations and auxiliary contacts available.
- Removable gland plate top & bottom (not on SPN).



Proline products are designed to offer quality, user friendly, practical and cost effective solutions for most indoor applications.



| Nominal Rating I <sub>e</sub> 415V | Reference | Fuse Type (included) | Ingress Protection | Dimensions mm |   |   |   |   |   |
|------------------------------------|-----------|----------------------|--------------------|---------------|---|---|---|---|---|
|                                    |           |                      |                    | H             | W | D | A | Ø | B |

| SP&N Switchfuses with 4 screw lid |          |       |      |     |     |    |         |  |     |
|-----------------------------------|----------|-------|------|-----|-----|----|---------|--|-----|
| 63A                               | SF63SPN  | 22x58 | IP41 | 250 | 115 | 60 | 25 cage |  | 100 |
| 80A                               | SF80SPN  | 22x58 | IP41 | 250 | 115 | 60 | 25 cage |  | 100 |
| 100A                              | SF100SPN | 22x58 | IP41 | 305 | 135 | 60 | 25 cage |  | 130 |

| TP&N Switchfuses with hinged door |       |       |      |     |     |     |         |    |     |
|-----------------------------------|-------|-------|------|-----|-----|-----|---------|----|-----|
| 20A                               | SF20  | 10x38 | IP41 | 300 | 180 | 110 | 10 cage |    | 80  |
| 32A                               | SF32  | 10x38 | IP41 | 300 | 180 | 110 | 16 cage |    | 80  |
| 63A                               | SF63  | BAO   | IP41 | 400 | 230 | 110 | 20      | M8 | 105 |
| 100A                              | SF100 | OSD   | IP41 | 400 | 230 | 110 | 20      | M8 | 105 |
| 125A                              | SF125 | TIS   | IP41 | 400 | 230 | 110 | 20      | M8 | 105 |

| TP&N 16kA MCCB with 4 screw lid |            |  |      |     |     |     |         |  |     |
|---------------------------------|------------|--|------|-----|-----|-----|---------|--|-----|
| 63A                             | MC T1 6/3  |  | IP41 | 400 | 230 | 110 | 50 cage |  | 150 |
| 80A                             | MC T1 8/3  |  | IP41 | 400 | 230 | 110 | 50 cage |  | 150 |
| 100A                            | MC T1 10/3 |  | IP41 | 400 | 230 | 110 | 50 cage |  | 150 |
| 125A                            | MC T1 12/3 |  | IP41 | 400 | 230 | 110 | 50 cage |  | 150 |
| 160A                            | MC T1 16/3 |  | IP41 | 400 | 230 | 110 | 50 cage |  | 150 |

| TP&N Load Break Isolators with hinged door |       |  |      |     |     |     |         |    |     |
|--|-------|--|------|-----|-----|-----|---------|----|-----|
| 20A  | LB20  |  | IP41 | 300 | 180 | 110 | 10 cage |    | 130 |
| 32A  | LB32  |  | IP41 | 300 | 180 | 110 | 16 cage |    | 130 |
| 63A  | LB63  |  | IP41 | 300 | 180 | 110 | 25 cage |    | 125 |
| 100A                                       | LB100 |  | IP41 | 400 | 230 | 110 | 20      | M8 | 150 |
| 125A                                       | LB125 |  | IP41 | 400 | 230 | 110 | 20      | M8 | 150 |
| 160A                                       | LB160 |  | IP41 | 400 | 230 | 110 | 20      | M8 | 150 |

- Alternative configurations, 3 or 4 pole + auxiliary contacts.
- Larger enclosures to suit customer's individual requirements together with IP65, Stainless Steel and GRP.

