

## Plug - STB 3/4-ST-5,08 - 1752043

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)

Plug component, Number of positions: 4, Pitch: 5.08 mm, Connection method: Screw connection with tension sleeve, Color: green, Contact surface: Tin

### Why buy this product



### Key Commercial Data

Packing unit	50 STK
GTIN	 4 017918 028367
GTIN	4017918028367
Weight per Piece (excluding packing)	11.710 g
Custom tariff number	85369010
Country of origin	Poland

### Technical data

#### Dimensions

Pitch	5.08 mm
-------	---------

#### General

Range of articles	STB
Type of contact	Female connector
Number of positions	4
Connection method	Screw connection with tension sleeve
Nominal cross section	2.5 mm <sup>2</sup>
Stripping length	8 mm
Screw thread	M3

#### Connection data

Minimum AWG according to UL/CUL	30
Maximum AWG according to UL/CUL	14

#### Standards and Regulations

Connection in acc. with standard	CSA
----------------------------------	-----

#### Environmental Product Compliance

# Plug - STB 3/4-ST-5,08 - 1752043

## Technical data

### Environmental Product Compliance

China RoHS	Environmentally Friendly Use Period = 50
	For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"

## Approvals


### Approvals


#### Approvals


CSA / UL Recognized / EAC

#### Ex Approvals

### Approval details

CSA		<a href="http://www.csagroup.org/services/testing-and-certification/certified-product-listing/">http://www.csagroup.org/services/testing-and-certification/certified-product-listing/</a>	13631
mm <sup>2</sup> /AWG/kcmil		28-14	
Nominal current I <sub>N</sub>		10 A	
Nominal voltage U <sub>N</sub>		300 V	

UL Recognized		<a href="http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm">http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm</a>	FILE E 60425
mm <sup>2</sup> /AWG/kcmil		30-14	
Nominal current I <sub>N</sub>		10 A	
Nominal voltage U <sub>N</sub>		300 V	

EAC		B.01742
-----	---	---------