

Accessories - FL 3-VS - 1760352

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://phoenixcontact.com/download)

PCB terminal block, Pitch: 2.5 mm, Number of positions: 3, Connection method: Slip-on connection, Mounting: Wave soldering, Color: green

Why buy this product

- The latching on the side enables various numbers of positions to be combined
- ☑ Well-known mounting principle allows worldwide use



Key Commercial Data

Packing unit	50 STK
GTIN	4 017918 030896
GTIN	4017918030896
Weight per Piece (excluding packing)	6.560 g
Custom tariff number	85369010
Country of origin	Poland
Note	Made to Order (non-returnable)

Technical data

Dimensions

Pitch	2.5 mm
Pin dimensions	0,8 x 1,0 mm
Pin spacing	5 mm
Hole diameter	1.3 mm

General

Range of articles	FL
Nominal cross section	0 mm²
Insulating material	PA 6.6
Solder pin surface	Sn
Flammability rating according to UL 94	V2
Number of positions	3

Standards and Regulations



Accessories - FL 3-VS - 1760352

Technical data

Standards and Regulations

Connection in acc. with standard	CSA
Flammability rating according to UL 94	V2

Environmental Product Compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e	
	No hazardous substances above threshold values	

Approvals

Approvals

Approvals

CSA / EAC / cULus Recognized

Ex Approvals

Approval details

CSA	®	http://www.csagroup.org/services/testing- and-certification/certified-product-listing/		13631
Nominal current IN			10 A	
Nominal voltage UN			300 V	

EAC	ERC		B.01742
-----	-----	--	---------

cULus Recognized	c 91 us	http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm		5-19770427
Nominal current IN			10 A	
Nominal voltage UN			300 V	

Phoenix Contact 2017 © - all rights reserved http://www.phoenixcontact.com